

FONDO PRIMER

It is a 2k high build, fast drying, primer surfacer based on special acrylic polyol resin used to fill imperfections and porosity and provide a good film thickness to sand and block surface to a smooth base paint.

Properties & Uses

- Used for steel surfaces.
- As a primer for auto paints
- Strong adhesion to steel surfaces, and fiber surfaces also.
- Fast drying, in short time, no dust pickup.
- Good sandability properties.
- Blocking surface and imperfections with sanding which leads to better topcoat finish.

TECHNICAL DATA/TYPICAL PROPERTIES

Specific Gravity	1.5 ± 2
Volume Solids	62 ±2
Spreading @ Thickness	15 to 20 m ² /ltr 40 to 50 microns
Drying time at 20 deg Dry To recoat @ sanding	20 to 30 minutes After 3 hrs minimum

Application Techniques

Can be applied using brush, roller, and spray gun, Thinning if necessary use general purpose thinner as needed

Mixing : **1 : 10.8 base to hardener**

Spray gun applicable, use appropriate thinner quantity and enough pressure for better atomization

Airless pressure should be 200 to 2500 psi
Nozzle Size 0.018" to 0.021"

Preparation

Prepare the surface well, surface should be clean from all dirt, grease/oil or any other contaminant or flakes, sanding well by hand or power brush, dry well no moisture for better adhesion

Health & Safety

Provided that reasonable standards are maintained & safe working practices followed, following the basic safety measures as good ventilation at application and drying, keep away of reach of childrenetc

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data.