



DECORATIVE COATINGS

VINOCOAT WB VINOLAC EXTERIER UNDERCOAT

IT IS GENERAL PURPOSE INTERIOR/ EXTERIOR PRIMER BASED ON SPECIAL ACRYLIC CO-POLYMERS WHICH GIVES EXCELLENT ADHESION AND ALKALAI RESISTANT PROPERTIES.

USES

It is recommended used for interior/exterior applications on concrete, plaster, bricks, asbestos, gypsum etc. as a masonry primer. It can be used for sealing the chalky surfaces like gypsum board and putty ...etc

TECHNICAL DATA

COLOUR, FINISH, V S% (ASTM D2697) SPECIFIC GRAVITY TSR RECOMMENDED DFT RECOMMENDED WFT FLASH POINT	White & Pastel colours Smooth / Matt 37 ± 2% 1.45 ± 0.05 12 – 10.5 M ₂ /LTR 30 – 35 Microns/Coat 80 – 95 Microns/Coat Water Base
---	--

Drying time @ 20 °C

TOUCH DRY	15 – 30 minutes
DRY TO RECOAT	1 – 2 hours
DRY TO OVER COAT	4 – 6 hours

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data. The company is not responsible of any caused damage to property or people due to unprofessional use of product

TECHNICAL DATA SHEET

APPLICATION INSTRUCTION

Before application, the surface should be sound, clean and free from oil, grease, loose particles, dust, etc. Application can be done by the recommended application methods.

APPLICATION DATA

APPLICATION METHOD	Roller, Brush, Spray
CLEANING/THINNING THINNER (VOLUME) CONV. SPRAY AIRLESS SPRAY NOZZLE SIZE MIXING RATIO POT LIFE	Water 10 – 25% depending Pressure : 2000 – 2500 psi 0.018” – 0.021” NA NA

Recommended system

VINOLAC SEALER PRIMER	1 COAT
OR	
VERLAC U/C/ PRIMER	1 COAT
VINOLAC FINE PUTTY	2 COATS
VINOLAC VINYL EMULSION	2 COATS
OR	
OTHER EMULSION TOPCOATS	
AS REQUIRED	





Haber Bldg, Rwees Street, Fanar Beirut Tel/Fax : 00961 1 696320 Email : infotec@hamcolb.com
Commercial branch Hazmieh-Martakla –Joseph Khoury bldg. -tel fax :+9615454292