

**VINOLAT S VINOLAC LATEX EMULSION SUPER EXTERIOR**

IT IS AN EXTERIOR ACRYLIC FULL LATEX PAINT BASED ON TOUGH BUT FLEXIBLE ACRYLIC POLYMER EMULSION RESIN WHICH FORMS CONTINUOUS SMOOTH MATT WASHABLE FINISH AND RESISTIBLE TO OUTDOOR WEATHERING CONDITIONS ,WITH VERY GOOD COLOUR STABILITY .

**Properties & Uses**

- A quality acrylic latex paint applied for wall and ceiling surfaces outdoor façade
- Unlimited colors can be
- Strong adhesion to surface
- Flat and smooth finish
- Provides a breathable surface for maximum durability
- Resistant to peeling and cracking
- Excellent color retention for exterior
- Very good alkali and UV resistant
- Excellent hiding properties
- Mildew resistant, not blistering
- Fast, simple clean up by water,
- minimum dirt pickup.

**Application**

Can be applied using brush, roller, and spray gun, Thinning if necessary use water about 25% One us gallon theoretically can cover about 45 to 60 m<sup>2</sup> depending on the surface porosity

Drying time about 1 to 2 hours under normal conditions and 5 to 6 hrs to recoat

**Disclaimer :** We warranty only the quality of our product and this data sheet is based on results obtained from experience and lab tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data. The company is not responsible of any caused damage to property or people due to unprofessional use of product .do not put in drain sewage. The manufacturer is not responsible of any damage caused to defect in application by the customer or a third party.

**Application Techniques**

Spray gun applicable, use appropriate water quantity and enough pressure for better atomization

Airless pressure should be 200 to 2500 psi  
Nozzle Size 0.018" to 0.021"

**Preparation**

Prepare the surface well, surface should be clean from all dirt, grease/oil or any other contaminant or flakes, dry well no moisture for better adhesion

**Health & Safety**

Provided that reasonable standards are maintained & safe working practices followed, there are no hazards in the handling of Vinolat SL semi Latex Emulsion paint following the basic safety measures as good ventilation at application and drying, keep away of reach of children ....etc