

VINOLAT SL VINOLAC SEMI LATEX EMULSION

IT IS AN INTERIOR ACRYLIC SEMI LATEX PAINT BASED ON TOUGH BUT FLEXIBLE ACRYLIC POLYMER EMULSION RESIN WHICH FORMS CONTINUOUS SMOOTH MATT WASHABLE FINISH.

Properties & Uses

- A quality acrylic latex paint applied for wall and ceiling surfaces
- Unlimited colors can be
- Strong adhesion to surface
- Flat and smooth finish
- Provides a breathable surface for maximum durability
- Resistant to peeling and cracking
- Excellent colour retention
- Very good alkali and UV resistant
- Excellent hiding properties
- Mildew resistant, not blistering
- Fast, simple clean up by water,
- minimum dirt pickup.

Application

Can be applied using brush, roller, and spray gun, Thinning if necessary use water about 25%

One us gallon theoretically can cover about 45 to 60 m² depending on the surface porosity

Drying time about 1 to 2 hours under normal conditions and 5 to 6 hrs to recoat

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data. The company is not responsible of any damage caused to properties or people due to unprofessional use

Application Techniques

Spray gun applicable, use appropriate water quantity and enough pressure for better atomization

Airless pressure should be 200 to 2500 psi
Nozzle Size 0.018" to 0.021"

Preparation

Prepare the surface well, surface should be clean from all dirt, grease/oil or any other contaminant or flakes, dry well no moisture for better adhesion

Health & Safety

Provided that reasonable standards are maintained & safe working practices followed, there are no hazards in the handling of Vinolat SL semi Latex Emulsion paint following the basic safety measures as good ventilation at application and drying, keep away of reach of childrenetc