

DECORATIVE COATINGS

TECHNICAL DATA SHEET

IT IS GENERAL PURPOSE INTERIOR/EXTERIOR PRIMER BASED ON SPECIAL ACRYLIC CO-POLYMERS WHICH GIVES EXCELLENT ADHESION AND ALKALAI RESISTANT PROPERTIES.AND ANTI FUNGIES PROPERTIES IF NEEDED.

VINOSEAL T FOR TRANSPARENT MILKY AND VINOSEAL C FOR **COLORED AND AF FOR ANTI FUNGIES**

USES

It is recommended used for interior/exterior applications on concrete, plaster, bricks, asbestos, gypsum etc. as a masonry primer. It can be used for sealing the chalky surfaces like gypsum board and putty, AF VERSION FOR ANTI FUNGIES ...etc

TECHNICAL DATA

COLOUR, Transparent//White & Pastel colours

FINISH,

Smooth / Matt

V S% (ASTM D2697)

 $37 \pm 2\%$

COVERAGE

10 TO 12 M₂/LTR

Drying time @ 20 °C

TOUCH DRY 15 - 30 minutes DRY TO RECOAT 1 - 2 hours

APPLICATION INSTRUCTION

Before application, the surface should be sound, clean and free from oil, grease, loose particles, dust, etc. Application can be done by the recommended application methods.

For Anti fungies surface must be well cleaned from fungies and well dried before application.

APPLICATION DATA

APPLICATION METHOD Roller, Brush, Spray

CLEANING/THINNING Water

THINNER (VOLUME) 10-25% depending CONV. SPRAY Pressure: 2000 – 2500 psi

AIRLESS SPRAY 0.018" - 0.021"

NOZZLE SIZE

NA MIXING RATIO POT LIFE NA

Recommended system

VINOLAC SEALER PRIMER 1 COAT OR ANTI FUNGIES VINOSEAL T/C AF VERLAC U/C/ PRIMER 1 COAT VINOLAC FINE PUTTY 2 COATS VINOLAC VINYL EMULSION 2 COATS

OTHER EMULSION TOPCOATS

AS REQUIRED

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data withoutprior notice. For surface preparation, safety details refer specifier and safety data.



Haber Bldg, Rwees Street, Fanar – Lebanon Tel/fax: 00961 1 696320 Commercial branche Hazmieh- Lebanon Tel/fax: 009615454292 www.hamcolb.com Email: infotec@hamcolb.com

