



DECORATIVE COATINGS

TECHNICAL DATA SHEET

VINOSEAL C100 /T100 PRIMER FOR TEXTURED FAÇADE PAINT

IT IS GENERAL PURPOSE INTERIOR/ EXTERIOR PRIMER BASED ON SPECIAL ACRYLIC CO-POLYMERS WHICH GIVES EXCELLENT ADHESION AND ALKALAI RESISTANT PROPERTIES.

VINOSEAL T100 T FOR TRANSPARENT MILKY AND VINOSEAL C100 FOR COLORED

USES

It is recommended used for interior/exterior applications on concrete, plaster, bricks, asbestos, gypsum etc. as a masonry primer for VINOTEX. It can be used on gypsum board and putty ...etc

TECHNICAL DATA

COLOUR,	Transparent//White & Pastel colors
FINISH,	Smooth / Matt
V S% (ASTM D2697)	37 ± 2%
COVERAGE	10 TO 12 M2/LTR
Drying time @ 20 °C	
TOUCH DRY	15 – 30 minutes
DRY TO RECOAT	1 – 2 hours

APPLICATION INSTRUCTION

Before application, the surface should be sound, clean and free from oil, grease, loose particles, dust, etc. Application can be done by the recommended application methods.

APPLICATION DATA

APPLICATION METHOD	Roller, Brush, Spray
CLEANING/THINNING	Water
THINNER (VOLUME)	10 – 25% depending
CONV. SPRAY	Pressure : 2000 – 2500 psi
AIRLESS SPRAY	0.018” – 0.021”
NOZZLE SIZE	
MIXING RATIO	NA
POT LIFE	NA

Recommended system

VINOSEAL T/C	1 COAT
VINOTEX	1COAT

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and lab tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data. The company is not responsible of any caused damage to property or people due to unprofessional use of product .do not put in drain sewage.



Haber Bldg, Rwees Street, Fanar –Lebanon Tel/fax : 00961 1 696320
Commercial branche Hazmieh- Lebanon Tel/fax : 009615454292
www.hamcolb.com Email : infotec@hamcolb.com