



## DECORATIVE COATINGS TECHNICAL DATA SHEET

### VINOSEAL 200 PA

Non yellowing Protective sealant for Scratched and Texture building Facades coating

IT IS GENERAL PURPOSE/ EXTERIOR SEALANT BASED ON SPECIAL ACRYLIC CO-POLYMERS WHICH GIVES EXCELLENT ADHESION AND ALKALAI RESISTANT PROPERTIES AND GIVES GOOD PROTECTION FOR THE BASE COAT AGAINST UV EFFECT .

#### APPLICATION INSTRUCTION

Before application, the surface should be dry and clean and freshly applied by first coat of VINOTEX M/G Maplexine or Monocouche –GRATIN not more than 48 hrs after application

#### USES

It is recommended used for exterior applications over VINOTEX M/G ,concrete, plaster, bricks, asbestos, gypsum etc. as a Sealant protection for building façades .

It can be used for sealing the chalky surfaces like gypsum board and putty ...etc.it helps to maintain the base coat and protect it from weather circumstances and UV to prevent from over-dusting and easy rain wash with good flexibility .

#### APPLICATION DATA

APPLICATION METHOD : Roller, Brush, Spray

CLEANING/THINNING : Water

WATER (VOLUME) : 10 – 25% depending

CONV. SPRAY : Pressure : 90 – 110 psi

AIRLESS SPRAY NOZZLE : 2000/2500PSI

SIZE MIXING RATIO : NA

POT LIFE : NA

Recommender system

Vinoseal 100 T/C 1<sup>st</sup> coat

or

Vinoseal 100 WP 1<sup>st</sup> coat

Vinotex G/M 2<sup>nd</sup> coat

Vinoseal 200 PA 3<sup>rd</sup> coat

#### TECHNICAL DATA

COLOUR : Milky transparent and white

FINISH :smooth

V S% (ASTM D2697): 40%+/-2

COVERAGE/COAT :10m2/liter (theoretical)

Drying time @ 20 °C

Touch dry :15-20Min

Dry to recoat :1-2hrs

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data.



Haber Bldg, Rwees Street, Fanar –Lebanon Tel/fax : 00961 1 696320

Commercial branche Hazmieh- Lebanon Tel/fax : 009615454292

[www.hamcolb.com](http://www.hamcolb.com) Email : [infotec@hamcolb.com](mailto:infotec@hamcolb.com)