



DECORATIVE COATINGS

TECHNICAL DATA SHEET

VINOSEAL 200

VINOLAC TEXTURE SEALANT

IT IS GENERAL PURPOSE/ EXTERIOR SEALANT BASED ON SPECIAL ACRYLIC CO-POLYMERS WHICH GIVES EXCELLENT ADHESION AND ALKALAI RESISTANT PROPERTIES AND GIVES EXCELLENT UV PROTECTION FOR THE BASE COAT .

USES

It is recommended used for exterior applications over maplexine ,monocouche, ,concrete, plaster, bricks, asbestos, gypsum etc. as a Sealant protection . It can be used for sealing the chalky surfaces like gypsum board and putty ...etc.it helps to maintain steady the color of the base coat and protect it from UV and help to prevent from overdusting .

TECHNICAL DATA

COLOUR,	Milky transparent and white
FINISH,	Smooth
V S% (ASTM D2697)	37 ± 2%
COVERAGE/COAT	10 TO 12 M ² /LTR

Drying time @ 20 °C	
TOUCH DRY	15 – 30 minutes
DRY TO RECOAT	1 – 2 hours

APPLICATION INSTRUCTION

Before application, the surface should be dry and clean and freshly applied by first coat of Maplexine or Monocouche note more than 48 hrs after application

APPLICATION DATA

APPLICATION METHOD	Roller, Brush, Spray
CLEANING/THINNING WATER (VOLUME)	Water
CONV. SPRAY AIRLESS SPRAY	10 – 25% depending Pressure : 90 – 110 psi
NOZZLE SIZE	2000/2500PSI
MIXING RATIO	0.018” – 0.021”
POT LIFE	NA
	NA

Recommended system

VINOLAC PRIMER	1COAT
VINOCOUCHE	1 COAT
OR	
VINOMAP	1 COAT
VINOSEAL	1COAT

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data.

