



DECORATIVE COATINGS

TECHNICAL DATA SHEET

VINOSEAL T/C SEALER PRIMER TRANSPARENT & COLORED

IT IS GENERAL PURPOSE INTERIOR/ EXTERIOR PRIMER BASED ON SPECIAL ACRYLIC CO-POLYMERS WHICH GIVES EXCELLENT ADHESION AND ALKALAI RESISTANT PROPERTIES.

VINOSEAL T FOR TRANSPARENT MILKY AND VINOSEAL C FOR COLORED

USES

It is recommended used for interior/exterior applications on concrete, plaster, bricks, asbestos, gypsum etc. as a masonry primer. It can be used for sealing the chalky surfaces like gypsum board and putty ...etc

TECHNICAL DATA

COLOUR,	Transparent//White & Pastel colours
FINISH,	Smooth / Matt
V S% (ASTM D2697)	37 ± 2%
COVERAGE	10 TO 12 M ₂ /LTR

Drying time @ 20 °C

TOUCH DRY	15 – 30 minutes
DRY TO RECOAT	1 – 2 hours

APPLICATION INSTRUCTION

Before application, the surface should be sound, clean and free from oil, grease, loose particles, dust, etc. Application can be done by the recommended application methods.

APPLICATION DATA

APPLICATION METHOD	Roller, Brush, Spray
CLEANING/THINNING THINNER (VOLUME) CONV. SPRAY	Water 10 – 25% depending
AIRLESS SPRAY	Pressure : 2000 – 2500 psi
NOZZLE SIZE	0.018” – 0.021”
MIXING RATIO	NA
POT LIFE	NA

Recommended system

VINOLAC SEALER PRIMER	1 COAT
OR	
VERLAC U/C/ PRIMER	1 COAT
VINOLAC FINE PUTTY	2 COATS
VINOLAC VINYL EMULSION	2 COATS
OR	
OTHER EMULSION TOPCOATS	
AS REQUIRED	

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data.



Haber Bldg, Rwees Street, Fanar –Lebanon Tel/fax : 00961 1 696320
Commercial branche Hazmieh- Lebanon Tel/fax : 009615454292
www.hamcolb.com Email : infotec@hamcolb.com



Haber Bldg, Rwees Street, Fanar –Lebanon Tel/fax : 00961 1 696320
Commercial branche Hazmieh- Lebanon Tel/fax : 009615454292
www.hamcolb.com Email : infotec@hamcolb.com