



DECORATIVE COATINGS TECHNICAL DATA SHEET

VINOSEAL 200 PA

Non yellowing Protective sealant for Scratched and Texture building Facades coating

IT IS GENERAL PURPOSE/ EXTERIOR SEALANT BASED ON SPECIAL ACRYLIC CO-POLYMERS WHICH GIVES EXCELLENT ADHESION AND ALKALAI RESISTANT PROPERTIES AND GIVES GOOD PROTECTION FOR THE BASE COAT AGAINST UV EFFECT .

APPLICATION INSTRUCTION

Before application, the surface should be dry and clean and freshly applied by first coat of VINOTEX M/G Mplexine or Monocouche –GRATIN not more than 48 hrs after application

USES

It is recommended used for exterior applications over VINOTEX M/G ,concrete, plaster, bricks, asbestos, gypsum etc. as a Sealant protection for building façades .

It can be used for sealing the chalky surfaces like gypsum board and putty ...etc.it helps to maintain the base coat and protect it from weather circumstances and UV to prevent from over-dusting and easy rain wash with good flexibility .

APPLICATION DATA

APPLICATION METHOD : Roller, Brush, Spray	Recommender system	
CLEANING/THINNING : Water	VINOTEX P/PWP	1 st coat
WATER (VOLUME) : 10 – 25% depending		
CONV. SPRAY : Pressure : 90 – 110 psi		
AIRLESS SPRAY NOZZLE : 2000/2500PSI	Vinotex G/M/S/R/RWP	2 nd coat
SIZE MIXING RATIO : NA	Vinoseal 200 PA	3 rd coat
POT LIFE : NA		

TECHNICAL DATA

COLOUR : Milky transparent and white
WHEN APPLIED TRASPARENT
FINISH :smooth
V S% (ASTM D2697): 50%+/-2
COVERAGE/COAT :10m2/liter (theoretical)
Drying time @ 20 °C
Touch dry :15-20Min
Dry to recoat :1-2hrs

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data.



Haber Bldg, Rwees Street, Fanar –Lebanon Tel/fax : 00961 1 696320
Commercial branche Hazmieh- Lebanon Tel/fax : 009615454292
www.hamcolb.com Email : infotec@hamcolb.com