



DECORATIVE COATINGS

TECHNICAL DATA SHEET

VINOTEX P/PWP SEALER PRIMER TRANSPARENT & COLORED FOR TEXTURED FAÇADE PAINT .

IT IS GENERAL PURPOSE INTERIOR/ EXTERIOR PRIMER BASED ON SPECIAL ACRYLIC CO-POLYMERS WHICH GIVES EXCELLENT ADHESION AND ALKALAI RESISTANT PROPERTIES.AND GOOD WEATHERING PROPERTIES FOR TEXTURED FAÇADE PAINT IT CAN BE IN WATER PROOF PROPRETIES AS VINOTEX PWP .

APPLICATION INSTRUCTION

Before application, the surface should be sound, clean and free from oil, grease, loose particles, dust, etc. Application can be done by the recommended application methods. For water proof version surface crakes must be well prepared and treated.

VINOTEX P FOR PRIMER OF TEXTURED FAÇADE PAINT AND VINOTEX PWP FOR WATER PROOF PROPERTIES

USES

It is recommended used for interior/exterior applications on concrete, plaster, bricks, asbestos, gypsum etc. as a masonry primer for outdoor textured paint . It can be used for sealing the chalky surfaces like gypsum board and putty concrete surface and as water proof primer for PWP version.

APPLICATION DATA

APPLICATION METHOD	Roller,
CLEANING/THINNING	Water
THINNER (VOLUME)	depending on surface
CONV. SPRAY	need
MIXING RATIO	
POT LIFE	NA
	NA

TECHNICAL DATA

COLOUR,	Transparent//White & Pastel colors
FINISH,	Rough
V S% (ASTM D2697)	85% ± 2%
Including powder charge	
COVERAGE If moderately diluted	4/6m2/kg

Recommended system

VINOTEX P PRIMER BY ROLLER	1 COAT
OR VINOTEX PWP	
VINOTEX/M/G/S/R/RWP	1 COAT
FOR VINOTEX M/G /S BY TOWEL	
VINOSEAL 200/PA BY SPRAY OR ROLL	1COAT

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without tprior notice. For surface preparation, safety details refer specified and safety data.



Haber Bldg, Rwees Street, Fanar –Lebanon Tel/fax : 00961 1 696320
Commercial branche Hazmieh- Lebanon Tel/fax : 009615454292
www.hamcolb.com Email : infotec@hamcolb.com