



## DECORATIVE COATINGS

## TECHNICAL DATA SHEET

### VINOTEX G

### MAPLIEXINE TEXTURE FAÇADE PAINT

A TOP QUALITY TEXTURED EMULSION PAINT MANUFACTURED FROM HIGH QUALITY AND CAREFULLY SELECTED RAW MATERIALS OFFERING GOOD PROTECTION FOR OUTDOOR FAÇADE BUILDING SURFACES, PROVIDING GOOD COVERING POWER AT A GOOD INVESTMENT COST IF COMPARED TO QUALITY , IDEALLY SUITED FOR CONTRACT PAINTING AND AVAILAVLE IN A WIDE RANGE OF TEXTURE AND COLORS TO COVER ANY DECORATIVE NEED.

#### Properties & Uses

- Wide color range
- Suitable for new concrete coating, cement, brick, stone and many other surfaces including soft board and hardboard, asbestos sheets.
- Exceptional ease of application which dries and gives scar texture effect with sandy touch effect.
- Excellent hiding power, good drying
- Excellent color retention
- Very good alkali resistant
- Resistant to fading and yellowing.

#### Application

Can be applied using special trowel and hopper spray gun or volumetric spray unit and than applied with trowel to give the texture effect ,Thinning if necessary use water in limited quantity

#### TECHNICAL SPECS

BINDER :Acrylic for outdoor use

Product type :Water base

Texture grain: medium fine

One pail/25kg theoretically can cover about 8 to 10m<sup>2</sup> depending on the surface situation .

Drying time about 1 to 2 hours under normal

#### Application Techniques

hopper gun applicable, use appropriate water needed quantity and enough pressure for better atomization nozzle 4to 6 mm

Volumetric unit with nozzle of 8 or 10mm Graco Tough Tek P30 Wagner PC 5 or equivalent.

#### Preparation

Prepare the surface well, surface should be clean from all dirt, grease/oil or any other contaminant or flakes, dry well no moisture for better adhesion  
Apply as a primer VINOSEAL 100 first coat than keep overnight than apply VINOTEX G.

#### Health & Safety

Provided that reasonable standards are maintained & safe working practices followed, there are no hazards in the handling of Vinolac Emulsion paint following the basic safety measures as good ventilation at application and drying, keep away of reach of children ....etc

conditions .

**NOTE:** We warranty only the quality of our product and this data sheet is based on results obtained from experience and lab tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data. The company is not responsible of any caused damage to property or people due to unprofessional use of product .do not put in drain sewage.



Haber Bldg, Rwees Street, Fanar –Lebanon Tel/fax : 00961 1 696320  
Commercial branche Hazmieh- Lebanon Tel/fax : 009615454292  
[www.hamcolb.com](http://www.hamcolb.com) Email : [infotec@hamcolb.com](mailto:infotec@hamcolb.com)