



DECORATIVE COATINGS

TECHNICAL DATA SHEET

VINOVI

VINYL EMULSION PAINT

A GOOD QUALITY EMULSION PAINT MANUFACTURED FROM GOOD QUALITY AND WELL SELECTED PIGMENTS OFFERING GOOD PROTECTION FOR INTERIOR SURFACES, PROVIDING HIGH COVERING POWER AT AN EXTREMELY ECONOMICAL PRICE, IDEALLY SUITED FOR COMMERCIAL CONTRACT PAINTING.

Properties & Uses

- Wide color range
- Suitable for new painted wall plaster, cement, brick, stone and many other surfaces including soft board and hardboard, asbestos sheets.
- Exceptional ease of application which dries to a very acceptable finish.
- Excellent hiding power, quick drying
- Good color retention
- Good alkali resistant

Application

Can be applied using brush, roller, and spray gun, Thinning if necessary use water about 10/25%

One us gallon theoretically can cover about 30 to 35m² depending on the surface porosity

Drying time about 1 to 2 hours under normal conditions and 5 to 6 hrs to recoat

Application Techniques

Spray gun applicable, use appropriate water quantity and enough pressure for better atomization

Airless pressure should be 200 to 2500 psi
Nozzle Size 0.018" to 0.021"

Preparation

Prepare the surface well, surface should be clean from all dirt, grease/oil or any other contaminant or flakes, dry well no moisture for better adhesion

Health & Safety

Provided that reasonable standards are maintained & safe working practices followed, there are no hazards in the handling of Vinolac Latex Emulsion paint following the basic safety measures as good ventilation at application and drying, keep away of reach of childrenetc

Available package Pail-IBC containers –plastic drums

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For surface preparation, safety details refer specifier and safety data. The company is not responsible of any caused damage to property or people due to unprofessional use of product .



Haber Bldg, Rwees Street, Fanar –Lebanon Tel/fax : 00961 1 696320
Commercial branche Hazmieh- Lebanon Tel/fax : 009615454292
www.hamcolb.com Email : infotec@hamcolb.com