





# WATERREPELL SR

# SOLVENTED SILICONE BASED WATERREPELLENT

#### **BENEFITS**

- Easily applied water repellent treatment.
- Gives hydrophobic surface to masonry.
- Ready to use
- Very strong water repellent.
- Economical and easy to use.
- Colourless, hence does not affect the natural finish of the buildings.
- Stops growth of algae, fungus etc. on walls.

#### **DESCRIPTION**

WATERREPELL SR is supplied as ready to use, colourless solvented silicon based liquid which imparts permanent water repellent effects. On porous surfaces WATERREPELL SR provides an invisible barrier to water penetration and remains effective for many years. WATERREPELL SR prolongs the clean appearance of buildings, reduces chemical attack, stops growth of algae, fungus and minimize efflorescence. It prevents leakage from brick, stone or concrete walls & dampening of walls due to rain. WATERREPELL SR penetrates deeply in to the surface and the active constituent hydrolyses, filling the pores with water repellent coating of silicones. The treatment does not block the pores and therefore 'breathing' properties of the wall are unaffected. Trapped moisture can easily be dried out. WATERREPELL SR is extremely effective and most surfaces require a single coat application. Due to the excellent water repellent properties of WATERREPELL SR, dirt and other atmospheric impurities are washed off by rain and its clean appearance is maintained for a longer period.

#### **APPLICATION**

All surface should be free from oil, grease, dust and other foreign materials. **WATERREPELL SR** is applied by brush or spray on dry surface. Treated surface should not receive moisture for 48 hours.

### **PACKING & COVERAGE**

**WATERREPELL SR** is available in 1, 5, 10, 50 & 100 ltrs carboys. 1ltr of **WATERREPELL SR** will cover 8 to 10 m<sup>2</sup> of the surface.

#### **SHELF LIFE & STORAGE**

**WATERREPELL SR** will have a shelf life of **12 months** in unopened containers when kept in dry conditions at a temperature between 5°C to 45°C. Storage at higher temperature or high humidity may reduce shelf life.

#### **HEALTH & SAFETY**

**WATERREPELL SR** is non-toxic and non-flammable. However, splashes on skin when occurs should be washed with water

## WATERREPELLSR



#### **QUALITY ASSURANCE**

Fairmate manufactures entire range of construction chemicals under compliance of ISO 9001, ISO (EMS) 14001 & OHSAS 18001 (Occupational Health and Safety) certified by ISOQAR / UK.

#### **TECHNICAL SERVICES**

While new advances and changes will take place but one thing will never change is quality and meeting special needs of our customers. Our technical personnel & experts are available to provide additional information and technical assistance. We are eager to work with you in development of new product and resolve your problem.

## **OUR RANGE OF PRODUCTS**

**CONCRETE ADMIXTURES** WATERPROOFING SYSTEMS **ENGINEERING GROUTS INDUSTRIAL FLOOR SURFACES** 

**CONCRETE REPAIRS SURFACE TREATMENT** PREPACKED CONCRETE MORTAR **PROTECTIVE COATING** 

**HIGHWAY REPAIR** LIOUID FLOOR WALL FINISHING SYSTEM

"Contact us to discuss any potential requirement and you will be assured of a rapid and effective response - that's guarantee !!"

Mfg. Under Licence of Fairmate UAE FZC





Haber Building, Rwess Street, Fanar

+961 1 696320 +961 5 454624

+961 5 454292 (Fax)

info@hamcolb.com beirut@fairmate.net





www.fairmate.com www.fairmateshoppee.com

**VENEZUELA** 

**INDIA** 

**DUBAI** 

NEPAL

**GHANA** 

**LEBANON** 

SAUDI ARABIA

**KENYA** 

**NIGERIA**